



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax:518.251.2908 www.Dura-Flex.com

## **PRODUCT SPECIFICATION**

**DURA-FLEX Part Number:** 14/7-2586

### **Product Description :**

A Fourteen(14) Gauge -- Seven (7) Conductor -- Bare Copper With PVC Insulation, Reverse Planetary Laid, , Rugged, Oil Resistant, PVC Jacketed, Yet Highly Flexible Instrumentation Cable.

### **Conductor Data:**

Material	Bare Copper
Gauge	14 AWG
Stranding	41 x 30

### **Insulation Data:**

Material	Polyvinylchloride
Nominal Wall Thickness	.022"
Diameter (primary)	.114"

### **Cabling Data:**

Number Of Conductors	7
Conductor Identification	Cond. 1            Red, No Number
	Cond. 2 - 6        White, Black Number
	Cond. 7            Green
O/A	Tissue Tape

### **Jacket Data:**

Material	Polyvinylchloride (Oil Resistant)
Color	Black
Markings	White Lettering, Also Indented
Nominal Wall Thickness	.055"
Diameter (O.D.)	.457"
Legend	CSL 14AWG 7/C RU AWM STYLE 20886 1000V 105C VW-1 E167231- B ---- CSA II/A/B 105C 600V FT1 234943 CE ROHS (DSC SEQ FT) TESTED FOR OIL RESISTANCE I/II + IMPACT AND CRUSH TO 1277 STANDARD

### **Product Ratings:**

Weight	.180 lbs./ft.
Temperature Range	-20°C to 105°C
Voltage	1000 Volts / 600 Volts
UL Approval	RU AWM STYLE 20886 1000V 105C
CSA Approval	CSA AWM IIA/B 105C 600V FTI
RoHS	RoHS Compliant
REACH	REACH 2007 Compliant