



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax:518.251.2908 www.Dura-Flex.com

PRODUCT SPECIFICATION

DURA-FLEX Part Number: 22/4WS Two Pair DMX-512

Product Description:

2 Pair 22 AWG Polyethylene Insulated General Purpose Shielded Cable UL AWM Listed Style 2919

Conductor Data:

Material	Tinned Copper
Gauge	22 AWG
Stranding	19 x 34

Insulation Data:

Material	Cellular Polyethylene
Nominal Wall Thickness	.016" Nominal
Diameter (conductor)	.062" Nominal

Cabling Data:

Number Of Pairs	2
Color Code	1st Pair -- Black And White 2nd Pair -- Red And Green

Shield Data:

Braid	36 AWG Tinned Copper Strands
Braid Coverage	90% Nominal
Foil	Aluminum / Polyester Tape
Drain Wire	22 AWG Tinned Copper Over Tape

Jacket Data:

Material	Highly Flexible Polyvinylchloride
Color	Black
Markings	White Lettering
Nominal Wall Thickness	.035" Nominal
Diameter (OD)	.290" Nominal
Legend	DURA-FLEX DMX RS-485 — 22 AWG 2-PAIR SHIELDED TYPE CL2 (UL) 75C FT4 E244628 OR CMG OR AWM 2919 LOW VOLTAGE COMPUTER CABLE — CSA AWM 1A/B80 150V FT1 701566 (SEQUENTIAL FOOTAGE)

Product Ratings:

Temperature	80°c (AWM), 75°c (CL2)
Voltage	150 Volts
Nominal Impedance	100 Ohms
Nominal Capacitance	14 - 15 pF/ft.
UL	AWM STYLE 2919, TYPE CL2 FT4
CSA	TYPE AWM