

# TWIST-LOCK® Devices

## 2 Pole, 3 Wire Grounding

20 Ampere, 125, 250 Volts and 277 Volts AC


### Safety-Shroud TWIST-LOCK® System



**HBL2320AR**



**HBL2320SR**



**HBL2320SR2**




**HBL2323**



**HBL2321S**



NEMA L5-20P  
20A 125V  
UL/CSA  
1 HP



NEMA L6-20P  
20A 250V  
UL/CSA  
2 HP\*



NEMA L7-20P  
20A 277V AC  
UL/CSA  
2 HP

### Safety-Shroud Twist-Lock Receptacles, Back Wired

Description	Catalog Numbers		
Angle housing one gang.	<b>HBL2310AR</b>	<b>HBL2320AR</b>	<b>HBL2330AR</b>
Surface mounting one gang.	<b>HBL2310SR</b>	<b>HBL2320SR</b>	<b>HBL2330SR</b>
Semi-flush two gang.	<b>HBL2310SR2</b>	<b>HBL2320SR2</b>	<b>HBL2330SR2</b>


Notes: See page B-72 for box mounting application.  
Housing and flange, gray Valox®.

### IP20 SUITABILITY

### Insulgrip Connector Bodies



NEMA L5-20P  
20A 125V  
UL/CSA



NEMA L6-20P  
20A 250V  
UL/CSA



NEMA L7-20P  
20A 277V AC  
UL/CSA

Description	Catalog Numbers		
Black and white nylon.	<b>HBL2313</b>	<b>HBL2323</b>	<b>HBL2333</b>

Note: Cord grip range .360"-.930" (9-24).

### IP20 SUITABILITY

### Safety-Shroud Male Plugs



NEMA L5-20P  
20A 125V  
UL/CSA  
1 HP



NEMA L6-20P\*  
20A 250V  
UL/CSA  
2 HP\*



NEMA L7-20P  
20A 277V AC  
UL/CSA  
2 HP


Description	Catalog Numbers		
Black and white nylon body, white Valox® shroud.	<b>HBL2311S</b>	<b>HBL2321S</b>	<b>HBL2331S</b>

Note: Cord clamp range .360"-.930" (9-24).

### Insulgrip® Flanged Inlets



NEMA L5-20P  
20A 125V  
UL/CSA



NEMA L6-20P  
20A 250V  
UL/CSA  
2 HP



NEMA L7-20P  
20A 277V AC  
UL/CSA  
2 HP

Description	Catalog Numbers		
Nylon casing, back wired.	<b>HBL2315</b>	<b>HBL2325</b>	<b>HBL2335</b>

Note: Only receptacles and plugs 480V AC or less are HP rated.

\*Also suitable for 208V AC.

HP ratings are AC only.

For technical information, see page B-83.

®Valox is a registered trademark of General Electric Company.