

TWIST-LOCK® Devices

2 Pole, 3 Wire Grounding

30 Ampere, 125 and 250 Volts
Safety-Shroud TWIST-LOCK® System



NEMA L5-30R
30A 125V
UL/CSA
2 HP



NEMA L6-30R
30A 250V
UL/CSA
2 HP*

Safety-Shroud Twist-Lock Receptacles, Back Wired

Description	Catalog Numbers	
Angle housing one gang.	HBL2610AR	HBL2620AR
Surface mounting one gang.	HBL2610SR	HBL2620SR
Semi-flush two gang.	HBL2610SR2	HBL2620SR2

Notes: See page B-72 for box mounting application.
Housing and flange, gray Valox®.



HBL2620AR



NEMA L5-30R
30A 125V
UL/CSA



NEMA L6-30R
30A 250V
UL/CSA

Insulgrip Connector Bodies IP20 SUITABILITY

Description	Catalog Numbers	
Black and white nylon.	HBL2613	HBL2623


Note: Cord clamp range .360"-.930" (9-24).



HBL2620SR



NEMA L5-30P
30A 125V
UL/CSA
2 HP




NEMA L6-30P
30A 250V
UL/CSA
2 HP*

Safety-Shroud Male Plug IP20 SUITABILITY

Description	Catalog Numbers	
Black and white nylon body, white Valox shroud.	HBL2611S	HBL2621S

Note: Cord clamp range .360"-.930" (9-24).



HBL2620SR2



NEMA L5-30P
30A 125V
UL/CSA
2 HP



NEMA L6-30P
30A 250V
UL/CSA
2 HP

Insulgrip Flanged Inlets

Description	Catalog Numbers	
Nylon casing, back wired.	HBL2615	HBL2625

Notes: Only receptacles and plugs 480V AC or less are HP rated.

*Also suitable for 208V.

HP ratings are AC only.

For technical information see page B-83.



HBL2623



HBL2621S

®Valox is a registered trademark of General Electric Company.