

Straight Blade Devices
2 Pole, 3 Wire Grounding
 15 and 20 Ampere, 125 Volts
INSULGRIP® Connector Bodies



HBL5269C



HBL8219C



Insulgrip Connector Bodies

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL5269C™	HBL5369C™
Corrosion resistant yellow nylon.	.230"-.720" (5.8-18.3)	HBL52CM69C	HBL53CM69C

Insulgrip Hospital Grade Connector Bodies

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL8219C™	HBL8319C
Transparent housing.	.230"-.720" (5.8-18.3)	HBL8219CT	HBL8319CT

Accessories

Seat-Tite® triple seal black elastomer cover for Insulgrip® connector bodies when used in a cord set.	HBL6018*
Same as above except yellow.	HBL60CM18*
Closure plug, black.	HBL6019
Closure plug, yellow.	HBL60CM19
PLUGOUT® lockout device for Hubbell plugs and others.	HLD

Notes: *IP55 suitability if closure plug inserted or when installed and used properly with HBL6017 or HBL60CM17.