



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax:518.251.2908 www.Dura-Flex.com

PRODUCT SPECIFICATION

DURA-FLEX Part Number: 08B15-8 4-Pair Cat 5E

Product Description:

4 Pair 24 AWG (7X32) Tinned Copper Insulated Shielded Cable UL AWM Listed Style 2919

Conductor Data:

Material Tinned Copper
Gauge 24 AWG

Insulation Data:

Material Cellular Polyethylene
Nominal Wall Thickness .032" Nominal
Diameter (conductor) .260" Nominal

Cabling Data:

Number Of Pairs 4
Color Code
P1 – Blue & White /Blue
P2 – Orange & White/Orange
P3 – Green & White/Green
P4 – Brown & White/Brown

Shield Data:

Braid 26 AWG 7/34
Braid Coverage 90% Nominal

Jacket Data:

Material Highly Flexible Polyvinylchloride
Color Black
Markings White Lettering
Nominal Wall Thickness .032" Nominal
Diameter (OD) .260" Nominal
Legend DURA-FLEX CAT5E TYPE – 24 AWG 4-PAIR SHIELDED -- (RU) AWM 2919
E167231-A 80C 30V LOW VOLTAGE COMPUTER CABLE --- CSA AWM IA/B
IIA/B 80C 30V FT1 701566 CE ROHS (SEQUENTIAL FOOTAGE)

Product Ratings:

Temperature 80°c (AWM)
Voltage 150 Volts
Nominal Impedance 100 Ohms +/- 15%
Nominal Capacitance 14 pF/ft.
UL AWM STYLE 2919 80C 30V
CSA TYPE AWM I/II A/B 80C 30V FT1

LAST REVISED: OCTOBER 2008